Sealing solutions for **ROTATING EQUIPMENT**

















Polymers and Sealing Solutions



MAKE THINGS WORK. BETTER.



Betech is a recognized supplier of gaskets, rubber seals, and polymer-based functional parts. With roots all the way back to early 20th century. Here, you find the broadest range in the industry. But feel free to expect even more.










Strong sales growth in the category of rotating elastomer seals causes us to expand the market offer by introducing mechanical seals and braided packings – accompanied by experienced technical support that our customers are used to.

On the following pages we present a complete range of competitive high-end sealing solutions for rotating equipment: Braided packings, mechanical seals, V-rings, oil seals and radial shaft seals.



Visit our website betech.site/rotating-seals



BRAIDED PACKINGS / GLAND PACKINGS

STANDARD BRAIDED PACKINGS

VALV

PUMP

POWER

ROTATING

LATTY has manufactured braided packings in France for over 100 years and always delivers high-performing products. LATTY composes the packings from more than 70 types of impregnation and 120 variants of quality yarns and wires.

PTFE - LATTYflon 3206

Made of 100 percent PTFE silk yarns, each single yarn being impregnated with PTFE. The packing is re-impregnated with a mixture of PTFE and inert lubricant during the braiding process.

Media PH values: 0 to 14. Working temperature: -200 to 280 °C.



Graphite – LATTYgraf T

Made of 100 percent pure and continuous graphite yarns, impregnated with a graphite mixture. Very low friction coefficient, good heat dissipation, and excellent elastic recovery. Suitable for high speed.

Media PH values: 0 to 14. Working temperature: -200 to 600 °C.



Aramide - LATTYflon 4788

Made of 100 percent aramide fibres. Each single yarn is impregnated with PTFE using an exclusive "Filcoat" process. Then re-impregnated with a mixture of PTFE and foodstuff-approved quality lubrication. Very high mechanical performance.

Media PH values: 2 to 13. Working temperature: -220 to 300 °C.



Vegetable - LATTYflon 1779

A plant-based packing made of anti-rot-treated high quality ramie yarns. Impregnated with a mixture of PTFE and lubricant during the braiding process.

Media PH values: 4 to 11. Working temperature: -40 to 120 °C.



Mixed - LATTflon 4757

A very strong multi-yarn packing. The corners are made of 100 percent aramide yarns impregnated with PTFE. The lubricated friction faces are made of 100 percent graphited PTFE. The entire packing is then re-impregnated with a mixture of PTFE and a lubricant. By combining the advantages of graphite, PTFE and aramide, this packing provides high mechanical resistance.

Media PH values: 2 to 14. Working temperature: -220 to 300 °C.



FLEXIBLE BRAIDED PACKINGS

PULP PAPER PUMP

WASTE

EXTRUDER

ROTATING SHAFT

LubSeal series by Nordic Seal is a fleksible packing with an elastomer core and an outer fibre braiding. A reservoir inside the hollow core makes it possible to add a lubricant to the seals. Pre-shrunk and ready to install. Extends service life. Developed and manufactured in Norway.



Elastomer cores

Choose between 3 elastomer cores: EPDM / NBR / Silicone each in 5 different hardnesses (Shore A).

Braiding

Choose between 3 different fibre materials:
Aramide / Polyamide / PTFE

Lubrication/Impregnation

Choose between graphite, PTFE or none (dry).

By mixing cores and braiding materials with or without lubrication, it's possible to configure a unique, customised sealing solution. The flexible braided packing is delivered as preformed rings. Various sealing profiles are possible.





MECHANICAL SEALS





Agitator seals are independent of direction of rotation, and manufactured as single or double seals. Available with or without bearing and suitable for top entry drives, bottom drives, and side mounted drives.

As option, connect a barrier fluid supply system for efficient cooling and continuous lubrication.

Ready to fit according to drawing and delivered as a factory tested unit. Can be manufactured and delivered in various sizes.

CARTRIDGE SEALS	FOOD PHARMA	PETRO CHEMICALS	PROCESS	WASTE WATER	PULP PAPER	POWER PLANT
	of rotation cartridge cooling ar Cartridge	seals are a ban, and manuf seals have a nd lubrication seals are avand are idea	actured as s n integrated n fluid. ailable in val	single or dou pump functions sizes a	ble seals. Do tion circulati and material	ouble ing the com-
	possible to	naintainance extend serv ution of brai	ice life. Carti	ridge seals a		

PUSHER SEALS	FOOD PHARMA	PETRO CHEMICALS	PROCESS	WASTE WATER	WATER SUPPLY	POWER PLANT
	food prod to work w Pusher se in a variet types, the For use in	er type is univuction equip ith media co als are indep y of sizes are steel spring high pressu pusher seal	ment. In adoption and solution of dispendent of dispendent of dispendent of the solution of th	dition, some ids. rection of roaterial comb dagainst the ons up to 25	otation, and a binations. In e media.	esigned available some

RUBBER BELLOW SEALS	FOOD PHARMA	PETRO CHEMICALS	PROCESS	WASTE WATER	WATER SUPPLY	POWER PLANT
	Universal to shaft d	nical seal for OEM pump r for use in all l effections. ance with ser in many matens.	manufacture kind of pump veral approv	er seal. os with plain rals/standard	shaft, non-se ds.	ensitive



BARRIER LIQUID SUPPLY SYSTEM

Barrier liquid supply systems are used together with double cartridge seal configurations.





Mechanical seals and support systems designed and manufactured by Flexaseal, a leading engineering company in the USA.

CARTRIDGE SEALS	FOOD PHARMA	PETRO CHEMICALS	PROCESS	WASTE WATER	POWER PLANT	BIOGAS
	and doubl bellow typ In addition	n, soft/hard ons are poss s (FFKM).	single or mu as well as ha	ulti spring so ard/hard sea	lutions, and	metal

SPLIT SEALS	PETRO CHEMICALS	PROCESS	WASTE WATER	ROTATING SHAFT	POWER PLANT		
		sy to install and jing and time					
	No other split cartridge design divides the sealing set into just integrated parts and makes the handling and installation as eas as this series.						
		y. No need f			d pressure tested at pecial tools, no shims		

METAL BELLOW SEALS	PETRO	PROCESS	POWER	CARGO		
METAL BELLOW SEALS	CHEMICALS PROCESS PLANT PUMP Low and high temperature edge-welded metal bellow so working pressure up to 20 bar and temperatures up to 4					
	using cen	of hydraulica trifugal force ontaining me	and therefo			



V-RINGS, OIL SEALS AND SHAFT SEALS

V-rings are one-piece all-rubber seals with V-shaped cross section. The elasticity of the V-ring ensures that its body is held securely in place against the shaft while the shaft rotation forces the soft lip against the counter face, forming a tight seal. V-ring applications can be found in many industries with rotating shafts, both as primary seal or as a safety secondary seal. V-rings are considered a cost effective choice with the additional benefit of absorbing considerable tolerances (irregular shaft roundness) better than many other shaft sealing technologies.

OIL SEALS	WIND POWER	ENGINE	TRANS- MISSION	AUTO- MOTIVE	ROTATING SHAFT	
	engine. The out and like machinery Oil seals a shaft seals An oil seal flexible rubenergizing Oil seals a	re used to see seal is preserved, gearbox, ending of the seal is prevent, gearbox, ending of the seal is provided are manufact in conditions	venting the nting contarngine etc. called greateals or simmensists of a makes the by e.g. a steament to DIN	oil or other luninants and place or dirt seater rings. The tell ring (hose sealing – in sealing – in seal spring.	ubricant fron particles to e als alternative older) bonded some cases a tandards, wi	n seeping enter the ely radial d to a additional

RADIAL PTFE SHAFT SEALS	FOOD PHARMA	PETRO CHEMICALS	PROCESS	ROTATING SHAFT		
	with a flex Usually, P the profile This gaske based sea	E shaft seals used that acts as let type is typils are not suiter dry running	ed in rotary a oil reservoir ically used for table due to	applications r. or rotating sl	have a groov	ve in rubber-

ADVANTAGES THAT BENEFIT YOU.

Betech is specialist in sealing solutions to OEMs, mechanical engineers, and service companies across all industries.

Together we create optimum solutions

In decisions about seals for rotating equipment, we need to know the five most critical application parameters:

- Fluid/Media Properties
- Working Pressure
- Working Temperature
- Rotation Speed
- Seal Chamber Dimensions

Based on this information, we specify and provide the optimum sealing solution whether it is a elastomer type of suitable quality, a braided packing or an advanced mechanical configuration.

Benefits, if you are **A MANUFACTURER** Reliable deliveries: Non-stop operations Proven quality at competitive prices: **High-performance solutions with** a great value/price ratio Replacement guarantee: **Continuous access to spare parts** enables long-term after-sales service Technical support: Specialist knowledge & advices Technical documentation: Fulfil customer expectations and requirements

Benefits, if you work

IN SERVICE & REPAIR

- Factory-to-Site service:
 Fast direct delivery
- High-end spare parts:

 Safe product choice and reliable solutions
- Extension of production uptime:

 Added customer value
- Technical Support:

 Specialist knowledge & advice
 - Recognition of work and reputation:
 - Great customer satisfaction and retention





PROCESS FOODTECH



ENERGY ENGINES TRANSPORT



AUTOMATION MACHINERY ENGINEERING



ELECTRONICS MEDTECH FURNITURE



We make things work better, and by improving your products or technical systems you become even more competitive.

The solution may be quite obvious or more complex, but our mission is always the same:

A partnership with Betech supports your business and contributes to more profitable operations and production.



Polymers and Sealing Solutions

Copenhagen

Betech A/S Vesterlundvej 4 <u>DK-2730 H</u>erlev

+45 44 85 81 00 info@betech.site betech.site

Sales & support Administration Purchasing

Esbjerg

Betech A/S Industrivej 29 DK-6740 Bramming

+45 76 56 26 00 info@betech.dk betech.dk

Sales & suppor Production Warehouse

Stavanger

Betech Skvadronveien 25 N-4050 Sola

+47 901 34175 info@betech.no betech.no

Sales & support

Qingdao

Codan Tech Qingdao Co. Ltd. Jinling no. 3, Jihongtan 266111 Qingdao, P.R. China

+86 532 8790 9757 info@codantech.com codantech.com

Sales & suppor Production Warehouse